

QMFZ2 Component - Plastics

Monday, November 24, 2003

E178416

RIALTI SRL

VIA ALLA PIANA 61 21018 SESTO CALENDE VARESE ITALY

Material Designation: **RIALFLAME B V0H 15H 20T**

Product Description: Polypropylene (PP), furnished as pellets.

Color	Min. Thick. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
ALL	1,6	V-0	-	-	-	-	-	-	-
CTI: -		HVTR: -		D495: -		IEC Ball Pressure (°C): -		-	
Dielectric Strength (kV/mm): -		Volume Resistivity (10 ⁹ ohm-cm): -				Dimensional Stability(%): -			
ISO Tensile Strength (MPa): -		ISO Flexural Strength (MPa): -				ISO Heat Deflection (°C): -			
ISO Tensile Impact (kJ/m ²): -		ISO Izod Impact (kJ/m ²): -				ISO Charpy Impact (kJ/m ²): -			

Report Date: 5/11/2003

Underwriters Laboratories Inc®

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.